

KR8

evolution

- DIFFERENTIAL CONTROLLER
- 3 DYNAMIC COLOUR LED DISPLAY
- ANALOGUE CONTROL OUTPUT
- INDEPENDENT TIMER
- SERVO MOTOR



FEATURES

DISPLAY		KR8
Dual LED	Main display: 4 digit h 11.7 mm. 3 colours: red, green and amber Secondary display: 4 green digit, h 7 mm	
INPUTS		
2 inputs	2 x Thermocouples: J (-50... +1000°C/-58... 1832°F), K (-50... +1370°C/-58... 2498°F), S/R (-50... +1760°C/-58... 3200°F), T (-70... +400°C/-94... 752°F)	
Accuracy	± 0.5% span ±1 digit, (±1% span ±1 digit for T/C S type)	
Digital inputs	1 or 2 according to instrument's part number (the 2nd digital input is alternative to OUT 4)	
OUTPUTS		
Up to 4	OUT 1: Relay SPDT 4A/240 Vac or voltage to drive SSR 13V max. @ 1mA, 10.5V min. @ 15mA ±10% or analogue galvanically isolated 0/4... 20 mA, 0/2... 10V (optional) OUT 2: Relay SPST-NO 2A/240 Vac or voltage to drive SSR 13V max. @ 1mA, 10.5V min. @ 15mA ±10% OUT 3: Relay SPST-NO 2A/240 Vac or voltage to drive SSR 13V max. @ 1mA, 110.5V min. @ 15mA ±10% OUT 4 programmable: voltage output to drive SSR 13V max. @ 1mA, 10.5V min. @ 22mA ±10% or transmitter supply or 2nd digital input	
FUNCTIONAL		
Control	PID single or double action, ON/OFF, ON/OFF with Neutral Zone Autotuning and Selftuning algorithms, Overshoot control	
Servomotor control	Available	
Alarms	3 alarms programmable as absolute, deviation, band	
Set Point	4 programmable Set Points	
Signal retransmission	Measuring or Set Point retransmission	
Serial communication	TTL (standard) + RS485 (optional), ModBus RTU protocol	
Baud rate	1200... 38400 baud	
EVOogreen	Stand-by mode of display, selectable	
Timer (optional)	Independent with 5 function modes	
GENERAL		
Power supply	24 Vac/Vdc ± 10%, 100... 240 Vac/Vdc -15%/+ 10% (50/60 Hz)	
Power consumption	7 VA max	
Dimensions / Weight	78 x 35 mm (1/16 DIN) - depth 69.5 mm / 200 g	
Mounting	Flush in panel in 45 x 45 mm hole	
Connections	24 screw terminals 2.5 mm ² (AWG22.... AWG14) fix, plug-in or clamp type	
Front protection degree	IP 65, mounted on panel with gasket	
Operating / storage temperature	0... 50°C (32... 122°F)/-20... +70°C (-4... 158°F)	
Operating humidity	20... 95 RH% without condensation	
Conformity	EN 61010-1, EN 61326	


HOW TO ORDER

To compose the part number, pls. choose one of the option for each variable

KR8	CODE
VERSION	
Controller	-
Controller + Timer	T
Controller + Timer + Programmer	P
POWER SUPPLY	
24 Vac/Vdc	L
100... 240 Vac	H
INPUT	
TC, RTD, mA, V, mV + digital input 1	C
TC, NTC, PTC, mA, V, mV + digital input 1	E
OUT 1	
Relay SPDT 4A	R
Vdc for SSR driving	O
0/4... 20 mA, 0/2... 10V galvanically isolated (control and retransmission)	I
OUT 2	
Relay SPST 2A	R
Vdc for SSR driving	O
Relay SPST 2A for Servomotor driving (*)	M
Not available	-
OUT 3	
Relay SPST 2A	R
Vdc for SSR driving	O
Relay SPST 2A for Servomotor driving (*)	M
Not available	-
OUT 4	
Digital input 2 or digital output or transmitter supply	D
RS485	
Available	S
Not available	-
CONNECTION	
Plug-in screw type	E
Plug-in screw type, fix part only	N
Clamp type	M
Fix screw type (standard)	-

(*) To purchase models with servomotor control, OUT2 and OUT3 must be completed with the code "M".

CONNECTIONS



DIMENSIONS

