

OPCMT

- TOUCH SCREEN OPERATOR PANELS
- TFT WIDESCREEN HIGH RESOLUTION
- BACKLIGHTED LED DISPLAY
- 7"



FEATURES

DISPLAY		OPCMT 2078X
Display		7" TFT
Resolution (pixel)		800 x 480
Brightness (cd/m ²)		400
Contrast ratio		800:1
Back Light type		LED
Colours		16.7 M
Touch screen		4 wire Resistive Type
Processor		Quad-core 64 bit RISC 1.5 GHz
MEMORY		
Flash (MB)		4 MB
RAM (MB)		1 GB
I/O PORTS		
USB Host		2.0 x 1
Ethernet		LAN1: 10/100 base-T x 1 LAN2: 10/100 base-T x 1
COM port		Con.A: COM2 (RS485 2 and 4w) – COM3 (RS485 2w) Con.B: COM1 (RS232 4w) – COM3 (RS232 2w)
RTC (on board)		Available
POWER SUPPLY		
Power supply		24 VDC ±20%
Power supply isolation		Available
Power consumption (mA @24VDC)		820
MECHANICAL		
Case		Plastic
Dimensions WxHxD		200.3 x 146.3 x 35 mm
Panel cut-out		192 x 138 mm
Weight		600 g
Protection degree		NEMA4/IP66
Mounting		On panel
Operating temperature		0°... 50°C (32°...122°F)
Storage temperature		-20°... 60°C (-4°...140°F)
Operating humidity		10...90% RH without condensation
SOFTWARE		
Software (optional)		Programmable with EasyBuilderPro Easy Access 2.0 (optional)
COMPLIANCE		
Conformity		CE, UL listed

HOW TO ORDER

OPCMT 2078X	
-EA	7" Operator panel with Easy builder Pro and Easy Access 2.0
--	7" Operator panel with Easy builder Pro

DIMENSIONS

