

ZTT

- DIN RAIL MOUNTING TRANSMITTERS
- PT100, TC OR UNIVERSAL INPUT



FEATURES

GENERAL	ZTT-51/GD	ZTT-52/GD	ZTT-53/GD	ZTT-50/GD
Input	2 or 3 wires PT100 Input and output isolated from each other.	mV and thermocouples K, J, E, N, T, R, S Input and output isolated from each other.	Universal, linearized for: 2 or 3 wires PT100, TC (K, J, E, N, T, R, S) mV, V, mA, Input and output isolated from each other.	Universal, linearized for: 2 or 3 wires PT100, TC (K, J, E, N, T, R, S, L, B, U, C, D, W) mV, V, mA, potentiometer. Input and output isolated from each other.
Range	-200... +800 °C			
Output	4... 20 mA 2 wires			
Options	SMART, programmable Programmable burnout, ranges and unit of measurement (°C - °F)		SMART, programmable with USB on the front Programmable burnout, ranges and unit of measurement (°C - °F)	
Programmability	With dedicated software and USB interface (optional)			
POWER SUPPLY				
Loop supply	10... 30 VDC		11... 30 VDC	
USB port	For power instrument and interface			
MECHANICAL				
Mounting	On DIN rail			
Dimensions	17.5 x 90 mm, depth 56.4 mm			22.5 x 106 mm, depth 120 mm

